IVECO AT380T38H, 6x4, Single Cabin, Manual Transmission, 380 HP, 33,000 KG GVW

BODY STRUCTURE

Made using aluminum profiles 6061 T6, fastened to a strong base structure made of stainless steel tubing.

STORAGE LOCKERS

Two (2) storage lockers, one on the R/H side and one on the L/H side of the vehicle

WATER & FOAM TANKS

15,000/400 Liters made of Polypropylene with life time warranty

FIRE PUMP

PTO Driven Low and high pressure pump centrifugal type, 3,800 LPM at 10 Bar and 400 LPM at 40 Bar made of gun metal

FOAM SYSTEM

Around-the-Pump" Foam Proportioning System 0 – 6 %, manual adjustable

MONITOR


Water / Foam monitor with jet/fog pattern, with output up to 3,800 LPM and throw range up to 65meters.


HOSE REEL


Manual Rewind hose reel fitted with High pressure rubber hose of 1" x 60m fitted with pistol type nozzle for normal pressure jet and fog patterns, 200 lpm at 40 bar, with foam pipe.

ACCESSORIES

Wide range of fire fighting accessories and equipments including, smoke ejector, hoses and nozzles.









HEAVY DUTY FIRE FIGHTING VEHICLE

NFM 150/4-SC





